



PRIMO

The compact ZETOR PRIMO HT 20 tractor mower offers perfect manoeuvrability, stability, and efficiency even under maximum workloads. It is available in an open version with a protective ROPS frame. The ZETOR PRIMO is especially suited to the maintenance of lawns and grass surfaces.

ENGINE

ZETOR PRIMO tractors are fitted with tried-and-tested 19 HP Yanmar engines that meet the latest Stage V emission standards. These three-cylinder, liquid-cooled engines provide the necessary power while offering quiet and fuel-efficient operations.

TRANSMISSION

Each ZETOR PRIMO tractor is equipped as standard with a two-speed hydrostatic gearbox. Dual pedal (forward and reverse) controls provide high comfort while driving. Equipping PRIMO tractors with this type of gearbox ensures smooth and quiet operation when working.

4WD

4WD is the standard equipment for PRIMO range. It allows small turning radius and high traction, for example when you use tractor in difficult conditions.

CUTTING DECK

The 54" cutting deck provided as standard guarantees effective mowing.

MODEL	UNITS	PRIMO HT 20 NC*
ENGINE		
Type	•	Yanmar - Diesel (Stage V)
Power (2000/25/EC)	kW	14.2
	HP	19.0
Fuel Tank	l	25
TRANSMISSION		
Type	•	HST
Number of Gears (F/R)	•	Infinite/2 Range
Max. Speed	km/h	13.3
Steering	•	Hydrostatic
HYDRAULICS		
Max. Total flow	l/min	26.4
THREE-POINT HITCH		
Type	•	I (N)
Max. Lift Capacity	kg	499
Control	•	Position
PTO		
Control	•	Electric/Hydro
PTO Mid	rpm	2,500
PTO Rear	rpm	540
DIMENSIONS		
Overall length, with 3PH	mm	2,394
Overall width	mm	1,130
Wheelbase	mm	1,350
Height to top of ROPS	mm	2,200
Min. Ground Clearance	mm	210
STANDARD TIRES		
Turf	•	18x8.00-10 26x12.00-12
ROPS & WEIGHT		
Roll Over Protection Standard	•	ROPS
Implement	•	54" Mower as a standard
Total Weight	kg	758

* NC = Cabrio